


24h water resistant

ARTICON L8 Technical data



plank dimensions mm	1383 x 214 mm		
plank thickness mm	8 mm		
bevels	4		
loc system	angle-snap loc system		
level of use according EN 10874	23 heavy domestic use / 32 general commercial use		
composition	top: direct laminated paper, impregnated with melamine resin core: moisture resistant high density fiberboard (HDF), treated with a water repelling coating backing: direct laminated paper, impregnated with melamine resin		
1 pack	9 planks - 2,66 m² - 19,4 kg		
1 pallet	48 packs - 127,86 m² - 958 kg		
residential warranty	20 years		
commercial warranty	3 years		
abrasion resistance	EN13329	AC5 (IP≥6000)	

abrasion resistance	EN13329	AC5 (IP≥6000)
impact resistance	EN13329	small ball : \ge 35 mm - big ball : \ge 600 mm
thickness swelling	ISO24336	≤ 18%
fire resistance	EN13501-1	Cfl-S1
formaldehyde emission	EN717-1	E1
slip resistance	EN13893	DS
density	EN323	900 kg/m³
resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
effect of a furniture leg	EN16581	no damage (foot type 0)
effect of a castor chair	EN425	no damage with type W wheels, 15.000 cycles
thermal resistance	ISO 8302	0,06 m ² .K/W Suitable for floor heating/cooling. Detailed instructior

Suitable for floor heating/cooling. Detailed instructions on www.waterresistantlaminate.org.

What is a laminate floor made of?



EN 14041 CCE Jacobie Constraints 23 23 DOP UP-DOPLASAT Berryalloc NV Industrielaan 100 8930 Menen, Belgium NB 1161 Laminate floor covering for use within building www.berryalloc.com







water resistant laminate floors